



Luminox Eco-Mini
Always in focus...

Technical Specifications*

	PRINCIPAL DOME	SATELLITE DOME
Central illuminance (at 1m distance)	60,000 lux	60,000 lux
Light field diameter (at 1m distance)	150 mm	150 mm
Depth of illuminance(L1 + L2)	700 mm	700 mm
Correlated color temperature	4,350 K	4,350 K
Color rendering index	93	93
Service life of bulb	50,000 h	50,000 h
Bulb power consumption	27 W	27 W
Power supply	100-240 VAC, 50/60 Hz	100-240 VAC, 50/60 Hz
Number of LED bulbs	9	9
Dimming range	5-100%	5-100%
Light head dimension	300 mm	300 mm
Carrier-arm Camera	Optional	Optional
Increase in Temp. near Surgeon's Head Area	< 1°C	< 1°C
Safety	MOSFET/PFA/OV	MOSFET/PFA/OV


Configurations



Mobile Stand



Ceiling Mount



Wall Mount

Optional Accessories



Standard
Monitor Arm



Advanced
Monitor Arm

Corporate Office



B-2/1, 8th Floor, Ashar IT Park, Wagle Estate, Rd. No.16,
Thane (W) 400 604, India

Tel : 022-2081 3711 | 022-2543 3711

info@matrixmedicals.in

Customer Care No.+91 93200 51023

Factory Address

R376, TTC Industrial estate, MIDC, Rabale,
Navi Mumbai, 400 701, India.

Tel : 022 2172 0091

priyal@prismsurgicare.com

www.prismsurgicare.com

